

# BKT Tandem

500 ÷ 1000 l - 8 ÷ 15 kW



BKT 119-500F-11T

Compressore con 2 gruppi pompanti bicilindrici traino cinghia, su serbatoi fissida 500 e 1000 litri.

Compressor with 2 belt-driven two-cylinder compressor pumps, stationary 500- or 1000-litre tank.

Kompressor mit 2 keilriemengetriebenen Aggregaten, auf 500- oder 1000 Liter Behälter.

Codice Code	Prodotto Product	L x D x H (cm)	kg	Lbs	tot.	
BRUN701FNM845	BKT 119-500F-11T	208 x 70 x 145	301	662,2	-	8017750189147
BRUN801FNM842	BKT 119-500F-15T	208 x 70 x 145	328	721,6	-	8017750189154
BTWN901FNN146	BKT 120-1000F-20T	237 x 83 x 176	529	1166,2	-	8017750241718

	Codice Code	Prodotto Product	Vol/Ph	kW	HP	Model	l/min, m <sup>3</sup> /h, c.f.m.	bar, p.s.i.	R.P.M.	n°	n°	dB(A)	L x D x H (cm)	kg	Lbs
	FISSI BISTADIO TRIFASE "TANDEM" TELEAVVIATI   STATIONARY STAR-DELTA DOUBLE-STAGE THREE-PHASE "TANDEM"   STATIONÄR STERN-DREIECK DOPPELSTUFE 3 PHASIG "TANDEM"														
500	BRUN701FNM845	BKT 119-500F-11T	400/3	4+4	5,5+5,5	2-BK119	1348 80,9 47,6	10 145	1220	2	2	83	200 x 60 x 125	267	588,6
500	BRUN801FNM842	BKT 119-500F-15T	400/3	5,5+5,5	7,5+7,5	2-BK119	1680 100,8 59,4	10 145	1250	2	2	83	200 x 60 x 120	294	648,2
1000	BTWN901FNN146	BKT 120-1000F-20T	400/3	7,5+7,5	10+10	BK120	2160 129,3 76,3	10 145	1100	2	2	83	225 x 80 x 155	482	1060,4

Sui modelli con avviamento stella-triangolo la centralina non è cablata.

On the star-delta models the control unit is not wired to the power connection.

Bei den Modellen mit Stern-Dreieck Schaltung ist lediglich die Stromzuführung bauseitig zu verlegen.

# BK Advanced

270 l - 4 ÷ 5,5 kW



BK 119-270V-7,5

Compressore bicilindrico traino cinghia lubrificato, su serbatoio da 270 litri fisso verticale. Completo di pressostato elettromeccanico con protezione termica tramite relè termico.

Lubricated belt-driven two-cylinder compressor with three-phase engine and 270-litre vertical tank. Electromechanical pressure switch with thermal relay protection.

Keilriemengetriebener Zweizylinder Kompressor mit 3-Phasen Motor und stehendem 270 Liter Behälter. Elektromechanischer Druckschalter mit thermischem Auslöser.

Codice Code	Prodotto Product	L x D x H (cm)	kg	Lbs	tot.	
BRNY701FNM854	BK119 - 270V - 5,5	86 x 85 x 210	160	379,5	-	8017750193793
BRNY801FNM884	BK119 - 270V - 7,5	86 x 85 x 210	172,5	379,5	-	8017750193816

	Codice Code	Prodotto Product	Vol/Ph	kW	HP	Model	l/min, m <sup>3</sup> /h, c.f.m.	bar, p.s.i.	R.P.M.	n°	n°	dB(A)	LwA	L x D x H (cm)	kg	Lbs
	BISTADIO TRIFASE CON SERBATOIO VERTICALE   DOUBLE-STAGE THREE-PHASE WITH VERTICAL TANK   DOPPELSTUFE 3 PHASIG AUF STEHENDEM BEHÄLTER															
270	BRNY701FNM854	BK119 - 270V - 5,5	400/3	4	5,5	BK119	674 40,44 23,8	10 145	920	2	2	79	-	72 x 72 x 177	144	317,5
270	BRNY801FNM884	BK119 - 270V - 7,5	400/3	5,5	7,5	BK119	840 50,4 29,7	10 145	1250	2	2	80	-	72 x 72 x 177	157	346,1