

EURARC 322



- Alternating current (AC) MMA electrode welding machine, 330A. Three-phase, 400V power supply. On wheels.-
- Usable electrodes: rutile up to 6 mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

The model has double secondary voltage for use also with basic and rutile electrodes.



TECHNICAL DATA

CODE	CODE 817014	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	V_{2PH}	TWO-PHASE MAINS VOLTAGE 400 V
F	MAINS FREQUENCY 50 / 60 Hz	A_{MIN}^{MIN} MAX AC	CURRENT RANGE IN AC 45 - 250 A	A_{MAX}^{MAX} 40°C AC	MAX CURRENT AC EN60974-1 250 @ 15 % A
A_{60%}^{60%} 40°C AC	AC CURRENT AT 60% 125 A	V_{0 AC}	MAX NO LOAD VOLTAGE IN AC 52 - 76 V	P_{MAX}	MAX ABSORBED POWER 9 kW
P_{60%}	ABSORBED POWER AT 60% 3,5 kW	φ	POWER FACTOR(cosphi) (cosphi) 0,4	∅_{MIN}^{MIN} MAX AC	D.USABLE ELECTRODES AC 1,6 - 5 mm
IP	PROTECTION DEGREE IP22	LxWxH	DIMENSIONS (LxWxH) 69 x 39 x 48 cm	kg	WEIGHT 37 kg

ON REQUEST ACCESSORIES



MMA WELDING KIT 250A 25 MMQ 3+2M AX25
801102

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST