

EURARC 410



- Alternating current (AC) MMA electrode welding machine, 330A. Three-phase, 400V power supply. On wheels.-
- Usable electrodes: rutile up to 6 mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

Electrodes: rutile.



TECHNICAL DATA

CODE	CODE 817016	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	V_{2PH}	TWO-PHASE MAINS VOLTAGE 400 V
F	MAINS FREQUENCY 50 / 60 Hz	A_{MIN} MAX AC	CURRENT RANGE IN AC 70 - 330 A	A_{MAX} 40°C AC	MAX CURRENT AC 300 @ 10% A
A_{60%} 40°C AC	AC CURRENT AT 60% 140 A	V_{0 AC}	MAX NO LOAD VOLTAGE IN AC 51 V	P_{MAX}	MAX ABSORBED POWER 12 kW
P_{60%}	ABSORBED POWER AT 60% 4,2 kW	φ	POWER FACTOR(cosphi) (cosphi) 0,75	∅_{MIN} MAX AC	D.USABLE ELECTRODES AC 2 - 6 mm
IP	PROTECTION DEGREE IP22	LxWxH	DIMENSIONS (LxWxH) 83 x 45,5 x 58 cm	kg	WEIGHT 45 kg

ON REQUEST ACCESSORIES



MMA WELDING KIT 300A 25 MMQ 4+3M AX50
801081

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST