

LINEAR 340



Aluminium

- Direct current (DC) MMA electrode welding machine, 320A. Three-phase, 230/400V power supply. On wheels.
- Usable electrodes: rutile, basic, stainless steel, cast iron, etc. up to 6 mm.
- Continuous adjustment of welding current.

DESCRIPTION

MMA, rectified, electrode welding machine in direct current (DC).

Stepless regulation of welding current.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.



TECHNICAL DATA

CODE	CODE 819020	V_{3PH}	THREEPHASE MAINS VOLTAGE 230 / 400 V	F	MAINS FREQUENCY 50 / 60 Hz
A_{MIN} A_{MAX} DC	CURRENT RANGE IN DC 60 - 320 A	A_{MAX} 40°C DC	MAX CURRENT DC EN60974-1 260 @ 35 % A	A_{MAX} 40°C DC	MAX CURRENT DC 320 @ 25 % A
A_{60%} 40°C DC	DC CURRENT AT 60% 180 A	V₀ DC	MAX NO LOAD VOLTAGE IN DC 65 V	P_{MAX}	MAX ABSORBED POWER 11,5 kW
P_{60%}	ABSORBED POWER AT 60% 7 kW	φ	POWER FACTOR(cosphi) (cosphi) 0,6	∅_{MIN} MAX DC	D.USABLE ELECTRODES IN DC 2 - 6 mm
IP	PROTECTION DEGREE IP22	LxWxH	DIMENSIONS (LxWxH) 89 x 46 x 59 cm	kg	WEIGHT 80 kg

ON REQUEST ACCESSORIES



MMA WELDING KIT 350A 35MMQ
4+3M AX50
801095



GOUGING KIT
802666

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST